



## **Professional Interphone HT-DZII**



- ◆ Automatic one-to-one 2-way hands-free communication.
- ◆ This product adopts mainframe and more ascendant congressional MIC is integrative. Appearance is handsome and voice is lifelike, clear and resonant
- ◆ Sub station has tone arm, could use exterior transmitter which is free to talk with master station.
- ◆ Individual volume controls for both master station and window sub station.
- ◆ Built-in recording signal output, can provide master station and sub station audio output for recording.
- ◆ Used in any places where conversations need to be assisted.
- ◆ Working Voltage: DC 12V 600mA
- ◆ Frequency response: 80Hz-14kHz
- ◆ Mic sensitivity:-42dB±2 dB

## **Professional Phantom Power 48V Power Supply Unit**



Model No. Parameter	HT-48V	HT-48V2	HT-320F Power Switcher Unit
Input Power	AC 110/220V	AC 110/220V	DC1.5V
Output Power	Phantom power 48V	Phantom power 48V	Phantom power 48V
Output Current	6.5mA	6.5mA	6.5mA
Compatible	Phantom power 48V	Phantom power 48V	Phantom power 48V
	microphone	microphone	microphone
N.W.	0.64 kg	0.64 kg	0.14 kg
Input Type	XLR×1	XLR×2	XLR×1
Output Type	XLR×1	XLR×2	XLR×1
Dimension	160×104×46	160×104×46	Diameter 22
(L×W×H)mm			Length 150
Color	Black	Black	Black

85